



F A S

L I T E L I F T

LITE LIFT

- Drawer up to 10 selections;
- Large pick-up pocket for easy withdrawal of products;
- Easy-to-clean linear design;
- Lift with single-axis movement for dispensing products without dropping;
- Configurable lift for each individual selection;
- Product pick-up door with automatic closure;
- Slide-in slide-out refrigerator unit with low consumption and quick replacement (patented), CO2 natural gas for maximum respect of the environment (GWP=1);
- Refrigeration with side ventilation to reduce consumption, minimise the effects of condensation and even out the internal temperatures of the dispenser (patented);
- Typical possible configurations:
1T - 2T Snack + Drink + Food also with MULTITEMP reconfigurable sideboard and 3T;
- intelligent lighting with high-efficiency LEDs and energy-saving function;
- Manage, programme, update, clone and audit functions with standard USB pen drive or remotely via Fas Cloud+;
- Interactive user interface with 10.1" tablet;
- Drawer displays (depending on configuration);
- Riella lock;
- Easy Click system to configure the machine quickly and easily without technical tools;
- Pre-cooling compartment;
- Product detection photocells;
- Full metal frame and drawers for solidity and durability;
- Integrated Wi-Fi.



R744



Dispensing lift

General Features		Lite Lift
Dimensions	mm (H x L x P)	1830 x 1060x 790
Open door encumbrance	mm	1810
Standard/max. number of drawers	nr.	6/7
Minimum internal temperature		+3°C with fridge safety on the bottom 3 drawers
Power supply	V/Hz	230/50
Rated refrigerator power	W	450
Weight	Kg	345
Refrigeration system	Compact N-class compression - Evap. Ventilated - Cyclic defrosting	
Interface	Tablet 10.1"	
Protocols	MDB/BDV/Executive	
Standard colour	Graphite grey scratch-resistant aluminium profile. Black surfaces - RAL 9005	



Fas International Spa
Via Lago di Vico, 60
36015 Schio · Vicenza · Italy
T +39 0445 502011

info@fas.it
www.fas.it

